



LUBRICANTS

Henry's premium lubricants lineup is designed for superior engine performance on outdoor power equipment. Depend on Henry's range of conventional, synthetic blend and full synthetic lubricants for excellent wear protection in the toughest conditions.

PREMIUM QUALITY OIL

Henry's line of premium oil is formulated specifically for 4-cycle engines used in outdoor power equipment, ensuring optimal performance and longevity.

Enhanced Protection: Our formula contains zinc and anti-foam additives, providing robust protection against wear.

Rust and Corrosion Resistance: Added rust and corrosion inhibitors shield critical engine parts from oxidation.

Thermal Stability: Thermal protection and extreme pressure additives provide peace of mind for high temperatures and prolonged use.

PRODUCT OVERVIEW:



OIL WEIGHT	TYPE	OPERATING RANGE °C	PINT (16 OZ)	QUART (32 OZ)	GALLON (128 OZ)
SAE 30	Conventional	-15C to <100C	H3055813	H3051743	
SAE 5W-30	Full Synthetic	-33C to <100C	H3059448	H3052610	H3053518
SAE 10W-30	Synthetic Blend	-33C to <100C		H3059017	H3053088
SAE 10W-40	Synthetic Blend	-27C to <100C		H3053996	H3050835
SAE 15W-50	Full Synthetic	-21C to <100C	H3051701	H3057631	H3058539
SAE 20W-50	Synthetic Blend	-15C to <100C		H3054905	
SAE 80W-90	Synthetic Blend Gear Oil	-27C to <60C		H3050792	

Henry's oil is sold in full case quantities. Pints (16 oz) sold in 12 pints per case. Quarts (32 oz) sold in 12 quarts per case. Gallon (128 oz) sold in 4 gallons per case. Safety Data Sheets (SDS) are available on www.henrysparts.com.

OPERATING TEMPERATURE RANGE

Operating Range (Cold Crank to Maximum Operating Temperature °F)

OIL WEIGHT	TYPE	OPERATING RANGE °C	-27°F	-20°F	-15°F	-10°F	-5°F	0°F	5°F	10°F	20°F	30°F	40°F	50°F	60°F	70°F	80°F	90°F	100°F	120°F	140°F	180°F	212°F
SAE 30	Conventional	-15C to <100C																					
5W-30	Full Synthetic	-33C to <100C																					
10W-30	Synthetic Blend	-33C to <100C																					
10W-40	Synthetic Blend	-27C to <100C																					
15W-50	Full Synthetic	-21C to <100C																					
20W-50	Synthetic Blend	-15C to <100C																					
80W-90	Synthetic Blend	-27C to <60C																					

* All engine oils meet API Service Category SL. Gear oil meets API Service Category GL-5. Refer to owner's manual for recommended lubricant specifications.